

System components Accessories



Device	LeckageSensor	Sounder	DustSensor
Type	KLS03	KFLASH-ETH	KDS01
Function	Sensor for the detection of water leaks	Flash alarm siren for optical-acoustic signaling of alarms	Sensor for the detection of dust deposits
Installation site	Floor, raised floor	Room	Rack, underbody
Room/system area	up to 100 sqm, cascadable up to 500 sqm	500 sqm	-
Configuration	AlarmManager, MultiSensor-LAN/TI	AlarmManager Web-Server	AlarmManager, MultiSensor-LAN/TI
Connection to Kentix system port	✓	✗	✓
ZigBee (radio)	✗	✗	✗
RFID (MIFARE® DESFire, Legic®)	✗	✗	✗
Integrated Web-Server (HTTP)	✗	✓	✗
Ethernet connection (10/100Mbit)	✗	✓	✗
PoE (Power over Ethernet)	✗	✓	✗
SNMP MIB (V2/3)	✓ (KAM)	✓	✓ (KAM)
SNMP Trap (V2/3)	✓ (KAM)	✓	✓ (KAM)
External power supply	✗	✓	✗
Alarm inputs (potential-free)	✗	✗	✗
Alarm inputs (potential-loaded)	✗	✗	✗
Analog inputs (4-20 mA, 1-10 V)	✗	✗	✗
Switching outputs (open collector)	✗	✗	✗
Sabotage monitoring	✗	✓	✓
Approvals	CE	CE	CE
Size (L x W x H in mm)	80 x 80 x 80	Ø93, H123	79 x 44

I/O-Module	I/O-Module	I/O-Module
KIO7052	KIO7053	KIO7017
Extension module for connecting external alarm messages	Extension module for connecting external alarm messages	Extension module for connecting external alarm messages
Distribution	Distribution	Distribution
-	-	-
AlarmManager Web-Server	AlarmManager Web-Server	AlarmManager Web-Server
✗	8	8
✗	8	8
✗	8	8
✓	4	4
✓	4	4
✓	4	4
✓ (KAM)	4 (KAM)	4 (KAM)
✓ (KAM)	4 (KAM)	4 (KAM)
✓	✓	✓
✗	16	✗
8	✗	✗
✗	✗	8
8	✗	4
✗	✗	✗
CE	CE	CE
72 x 123 x 35	72 x 123 x 35	72 x 123 x 35